


Bekafix® posts

Posts

Profile posts, polyester coated on galvanised with fixing system to be used with multiple panels.

Product detail



BENEFITS

- Very attractive symmetrical shape, patent protected
- Fixing system almost not visible
- Steps for slopes: 2,5 cm
- Ideal for all panels in medium security
- Perfect for installation with concrete plate

Profile

- Tubular post, profiled in "H" shape, plate thickness: 1,25 mm
- With 3 pre-drilled holes for fixing of the special metal security clips with bolts
- With punched holes for positioning and fixing of the panels by means of fixing clips
- Cross section of the post: 70 x 44 mm
- I/V: 5.28 cm³
- Cap with hook to support panels during installation

Accessories

- Security fixation system: plastic coated metal clip with as an option stainless bolt with nut with break-off head
- Metal or polyamide fixing brackets
- Bekafix installation tongs
- Floor plate
- Connection piece to create bent arm for panels
- Single or double bent arms

Coating technique

Galvanised: inside and outside and polyester coated (minimum 60 microns)



Colours

Green RAL 6005 and grey RAL 7016

Other colours are available on request.

ASSORTMENT BEKAFIX® POSTS

Panel height mm	Post length mm		Numer of fixators/post (intermediate/corner post*)
	Concrete	Baseplate	
630	1075	675	2 x 2
830	1275	-	2 x 2
1030	1475	1075	2 x 2
1230	1675	1275	2 x 3
1430	1975	-	2 x 3
1530	1975	1575	2 x 3
1630	2175	1675	2 x 3
1730	2175	1775	2 x 3
1830	2475	1875	2 x 4
1930	2475	1975	2 x 4
2030	2575	2075	2 x 4
2230	2775	-	2 x 4
2430	3175	2475	2 x 4

Compatible products

- All Nylofor panels
- CreaZen
- Decofof



* end post = only half of the numbers of fixators necessary