



Nylofor® 3D Multi

Panels

Nylofor 3D Multi is a multifunctional fencing system developed for a professional and cost efficient installation.

Product detail



BENEFITS

Multifunctionality

Heavy welded mesh panels with rectangular meshes and horizontal curves guarantee a good level of rigidity. The Nylofor 3D Multi panel has been designed to offer a system that can be applied in a multitude of applications at an attractive price. The 2.5 m wide panels are available in multiple RAL colours.

High longevity

Betafence's coating technology guarantees an extra high longevity. After galvanising a special layer is applied for a perfect adhesion of the polyester coating.

Excellent price/quality rate

Nylofor 3D Multi is a quality product offered at an attractive price.

Complete system

The system consists of panels in various heights and can be installed on multiple post systems. A wide assortment of swing and sliding gates completes the fence.

Security level



Applications



Functionalities



Post and fixing systems



Square post system

The panels are fixed on the front side of the posts by means of fixators and security bolts. The welded square tubular posts (60 x 60 mm) have inserts for fixing the panels with the fixators and are covered with a plastic cap.



Bekafix post system

The panels are fixed laterally onto the posts and secured with anti-vandal metal security fixators. The H-shape welded tubular posts (70 x 44 mm), are galvanised and PES coated and supplied complete with accessories and a polyamide cap.



Quixolid Plus post system

Lateral fixing of the Nylofor 3D Multi panels in the Quixolid Plus post, without accessories. Perfect fixing of the curves of the panel in the post profile. The Quixolid Plus posts (75 x 50 mm + slots every 100 mm) are covered with a plastic cap.

For technical details on different post systems: cfr. specific pages on posts in this catalogue.

Panels

The panels have a width of 2500 mm and are available in a range of heights: from 1030 to 2030 mm. The panels have vertical barbs of 30 mm at one side, the barbs can be placed at the top or at the bottom. The horizontal curves give the panels extra rigidity. The meshes are 200 x 50 mm, meshes at the curves 100 x 50 mm. The horizontal wire diameter is 5 mm, the vertical wire diameter is 4 mm.

Gates

The Nylofor 3D Multi panels can easily be combined with Robusta swing- and sliding gates.

Coating technique

Panels made out of galvanised wires. A pre-treatment process guarantees a perfect PES-coating adhesion to the product surface.



Colours

The panels are available in green RAL 6005, anthracite grey RAL 7016 and RAL 9010. Other RAL colours upon request.

ASSORTMENT NYLOFOR 3D MULTI

Fence height mm	Panels width x height mm	Number of curves per panel
1030	2500 x 1030	2
1230	2500 x 1230	2
1530	2500 x 1530	3
1730	2500 x 1730	3
1930	2500 x 1930	3
2030	2500 x 2030	4

* adapted lengths for Quixolid Plus and Bekafix posts

