


## Round posts

### Posts

Professional round metal posts, galvanised and plastic coated.

### Product detail



### BENEFITS

- Standard system for welded fences and chainlink.

#### Description

Round tubular posts, posts with postlength > 3.10 m are foreseen with holes every 49,5 cm for fixing the wire holders (wire holders to be ordered separately) with cap

#### Coating technique

Galvanised in-and outside (275 g/m<sup>2</sup> - both sides combined) and plastic coated (min. 60 micron)



#### Accessoires

Galvanised in-and outside (275 g/m<sup>2</sup> - both sides combined) and plastic coated (min. 60 micron)

#### Colours

Green 6005, some types also in black 9005

ROUND POSTS* (CORNER AND INTERMEDIATE POSTS)						
Post diameter (mm)	Ø 38	Ø 38	Ø 42	Ø 48	Ø 48	Ø 60
Plate thickness (mm)	1,25	1,5	1,5	1,25	1,5	2
Post length (mm)						
1500	•					
1750	•			•		
2100			•	•**		
2200						•**
2400					•**	
2500						•**
2600					•**	
2700						•**

\* Round tubular posts, with 1 wire holder and cap with Betafence logo    \*\* also in black RAL 9005

ROUND PROFESSIONAL POSTS						
3100					•	
3250						•
3500					•	•
3750					•	•
4750						•
6000						•

Round tubular posts with holes every 49,5 cm for fixing the wire holders (wire holders to be ordered separately) with cap

ROUND POSTS WITH BENT ARM						
3100					•	
3250						•

Bent arm: length 45 cm, bent under a corner of 40°, with 3 holes for wire holders, with cap. Vertical part with inserts every 49,5 cm for wire holders and tension wires.

BRACE POSTS FOR BEKACLIP AND ROUND POSTS						
1500	•					
1750	•					
2200		•**				
2700		•**				
3000		•				
3500					•	
4000					•	
4750					•	

\*\* also in black RAL 9005 - Corner of the brace posts: 35° (Ø 38) – 47° (Ø 48) - Complete with fixing bolt for fixing to the brace and corner posts.

### Compatible products

- Pantanet
- Fortinet
- Plasitor

