


## Bekafix® posts

### Product detail



### Posts

Profiled posts, polyester coated on galvanised with fixing system to be used with multiple panels.

#### BENEFITS

- **Very attractive symmetrical shape, patent protected**
- **Fixing system almost not visible**
- **Steps for slopes: 2,5 cm**
- **Ideal for all panels in medium security**
- **Perfect for installation with concrete plate**

#### Profile

- Tubular post, profiled in "H" shape, plate thickness: 1,25 mm
- With 3 pre-drilled holes for fixing of the special metal security clips with bolts
- With punched holes for positioning and fixing of the panels by means of fixing clips
- Cross section of the post: 70 x 44 mm
- **II/V: 5.28 cm<sup>3</sup> | Yield strength: 250 MPa | Relative strength: 132**
- Cap with hook to support panels during installation

#### Accessories

- Security fixation system: plastic coated metal clip with as an option stainless bolt with nut with break-off head
- Metal or polyamide fixing brackets
- Bekafix installation tongs
- Floor plate
- Connection piece to create bent arm for panels or extension
- Single or double bent arms

#### Coating technique

Galvanised: inside and outside and polyester coated (minimum 60 microns)



#### Colours

Green RAL 6005 and grey RAL 7016

Other colours are available on request.

#### ASSORTMENT BEKAFIX® POSTS

Panel height mm	Post length mm		Numer of fixators/post (intermediate/corner post*)
	Concrete	Baseplate	
630	1075	675	2 x 2
830	1275	-	2 x 2
1030	1475	1075	2 x 2
1230	1675	1275	2 x 3
1430	1975	-	2 x 3
1530	1975	1575	2 x 3
1630	2175	1675	2 x 3
1730	2175	1775	2 x 3
1830	2475	1875	2 x 4
1930	2475	1975	2 x 4
2030	2575	2075	2 x 4
2230	2775	-	2 x 4
2430	3175	2475	2 x 4

Europe  
Blokkestraat 34b  
B-8550  
Zwevegem  
Tel: +32 56 73 46 46

USA  
3309 SW Interstate 45  
Ennis,  
TX 75119  
Tel: +1 972 878 7000

Middle East  
P.O. Box 293517 DAFZA,  
Building E 5, Block A  
8th Floor, Office 802  
Tel: +971 04 6091122

Africa  
B10, Bergriver Business Park  
Paarl,  
7646  
Tel: +27 021 868 7300