




Bekafix® Ultra posts

Product detail



Compatible products

- All Nylofor panels (in superposition) up to 4 m
- CreaZen panels
- Securifor panels up to 3 m

Posts

A higher rigidity profiled post, for medium to high security applications, at an excellent price-quality ratio.

BENEFITS

With the Bekafix Ultra post, all the benefits of the standard Bekafix post are kept, but by increasing the inertia considerably, its application range has become much wider.

- Quick installation
- Concrete plates maintained directly in between the posts, without any plate holders
- Same accessories as the standard Bekafix posts
- 10 Years guaranty in Extreme conditions

Profile

- Tubular post, profiled in "H" shape, cross section of the post: 70 x 44 mm, plate thickness: 1.75 mm
- With central holes every 15 cm, for fixing of the special metal security clips with bolts
- With side punched holes for positioning and fixing of the panels by means of fixing clips
- I/V: 7.29 cm³ | Yield strength: 550 MPa | Relative strength: 401
- Post cap with hook to hang panels for ease of installation.

Accessories (same as Bekafix Standard post)

- Fixing system: plastic coated metal clip with, as an option, one-way security bolt or PA standard clips.
- Bekafix installation plier
- Spider fixing for installation of Securifor panels
- Base plate for installation on tiles or concrete floor
- Connection piece to create bent arm for panels or extension
- Single or double bent arms for Bekafix range

Coating technique

Magnelis®: inside and outside and polyester coated (minimum 100 microns).



Colours

Green RAL 6005, Black RAL 9005, Anthracite RAL 7016 and White RAL 9010
Other colours are available on request.

BEKAFIX® ULTRA POSTS

Fence height mm	Post length mm	Number of fixators per intermediate post	Number of fixators per end post
1930*	2475	8	4
2030	2575	8	4
2430	3175	8	4
3000	3775	10	5
4000	4775	12	6

* The same post can be used for installation in concrete or footplate

Other heights available on request

Europe
Blokkestraat 34b
B-8550 Zwevegem
Tel: B: +32 56 73 46 46
Tel: NL: 0800 022 76 98

USA
3309 SW Interstate 45
Ennis,
TX 75119
Tel: +1 972 878 7000

Middle East
P.O. Box 293517 DAFZA,
Building E 5, Block A
8th Floor, Office 802
Tel: +971 04 6091122

Africa
B10, Bergriver Business Park
Paarl,
7646
Tel: +27 021 868 7300