

HoriZen® system Swing gates


Access control

Swing gate with or without HoriZen Prime (XL) Composite infill

Product detail



single swing gate



double swing gate

BENEFITS

Composite or no infill

For a perfect match with the HoriZen Prime (XL) WPC infill, the gates can be ordered with the available Composite boards. Or the gates can be ordered without any infill leaving you to apply an alternative infill of your choice (20 mm).

High quality

- Rigid steel frame construction
- Mitre corner welded frame
- Qualitative stainless steel gate hardware, with built in lock

Large and flexible range

The swing gates are available with the HoriZen Prime infill. The standard size of the single swing gate is 100 cm wide x 180 cm high. The frame and the posts of the gate are available in RAL 7016 S (structured). The gate has a universal opening direction. We can offer double swing gates with a maximum width of 4M wide on request.

Easy installation

Universal opening direction, which can be determined on moment of installation

Advantages

CE certified | Universal opening direction | Strong and rigid construction | Front and back of the gate look the same | Aesthetically pleasing | High quality accessories add ons and options possible

Applications



Functionalities



Frame

Standard single swing gates (980 x 1845 mm)

- Steel frame, profiles 60 x 60 mm
- Mittre welded construction
- Polyester coated frame in anthracite
- Anodized and polyester coated profiles (to hold the infills)

Posts

- Set of 2 steel posts (single gate : hinge post & latch post ; double gates : 2 hinge posts) of 100 x 100 x 3 mm ; if wing width is > 1,5m post section : 120x120x3 mm
- Hot dip galvanised and polyester coated in RAL 7016 S
- Post length 2600 mm for installation in concrete

Infills

HoriZen Prime Composite

- Anthracite color
- Brown color
- Sand color
- Grey color
- No infill
- Decorative boards

Range

Single swing gates:

- Standard size 1000 x 1800 mm
- Non- standard sizes:
 - * Single swing gates wing width between 980 mm and 1930 mm (max)
 - * max. wing height 1845 mm

Double swing gates:

- Max double gate width: 4000 mm x 1800 mm high
- Non-symmetrical wing width are possible with a maximum wing width of 1930 mm/wing

Accessoires

- Built in lock with 80 mm Cylinder
- 2 Decorative Stainless Steel Handles
- A U profile for the fixation of the WPC infill to the gate posts (U profile available in RAL 7016 S)



Lock & cylinder



Handles



Catcher



Hinges

STANDARD HORIZEN SINGLE SWING GATES

Infill	Type	Boards available colors	Gate frame available colors	Gate posts available colors	wing width mm	wing height mm	post distance (center/center) mm	required space mm
Composite	Prime (XL)	anthracite almond brown sand grey	anthracite RAL 7016 S	anthracite RAL 7016 S	980	1845	1130	1230
without infill	-	-	anthracite RAL 7016 S	anthracite RAL 7016 S	980	1845	1130	1230

Europe
Blokkestraat 34b
B-8550 Zwevegem
Tel: B: +32 56 73 46 46

USA
3309 SW Interstate 45
Ennis, TX 75119
Tel: +1 972 878 7000

Middle East
P.O. Box 293517 DAFZA, Building E 5,
Block A 8th Floor, Office 802
Tel: +971 04 6091122

Africa
B10, Bergriver Business Park
Paarl, 7646
Tel: +27 021 868 7300

Betafence is the world market leader in fencing solutions, access control and detection for perimeter protection. All Betafence companies and product names are trademarks owned by PRÆSIDIA Group Limited. Modification in products and assortment are subject to change without prior notice. Proud to be a PRÆSIDIA brand, Betafence is part of a global network, working alongside Guardiar and Hesco as a leader in perimeter security systems and solutions. For more information please visit praesidiad.com.

BETAFENCE
Securing What Matters
betafence.com/contact