


## The Guardian Fence System®

The first system to provide a total security solution, with seamless security integration, easy installation, upgrade, repair, and maintenance.


With the industry's widest available range of rigid metal security meshes options, Betafence provides you with the flexibility to choose a security barrier that best fits your project's requirement.

The revolutionary design of the patented Guardian Fence System® allows for any of these mesh styles to be incorporated into a fence or partition barrier.




### **DUTYGUARD**

This welded wire mesh provides medium-to-high security features, while also providing good visibility through the mesh. Choose from a wide selection of mesh apertures and wire diameters.




### **SECURIGUARD**

This woven wire mesh is capable of adjusting to steep slopes and the contours of a landscape. We offer a variety of styles, providing high-security protection and superior aesthetic appeal.




### **SENTRYGUARD**

Either with a powder coat finish, or galvanized, this expanded metal mesh comes in a variety of diamond-shaped sizes to deter cutting and climbing.




### **LOUVERMESH™**

Among the most secure meshes available, our exclusive LouverMesh™ deters both cutting and climbing. This mesh allows airflow and provides a high degree of visual screening.




### **STRIKEGUARD**


Made from solid steel or aluminum panel, this mesh type is extremely strong, and resists cutting and climbing. The perforated panel provides unique visual appeal, and is available with powder coat finish.





### **SECURIFOR 4D**


A heavy weldmesh panel when a high level of security is needed. The front and back alternating wires offers increased rigidity and protection ideal for combining security, detection and surveillance.


Description	Name	Size	Screening %	% Open Area	Thickness (Inches)		Lbs. per 100 S.F.		Short Opening Size (Inches)	Long Opening Size (Inches)	
					Wire Thickness		Plain	Galvanized			
 DutyGuard Welded Wire	Duty 2-8	2" x 8ga	16.00%	84.00%	0.162		98	105	1.838	1.838	
	Duty 3-5-8	3" x 1/2" x 8ga	36.00%	64.00%	0.162		210	225	0.338	2.838	
	Duty 3-5-6	3" x 1/2" x 6ga	48.00%	52.00%	0.192		278	298	0.308	2.838	
	Duty 3-5-4/8	3" x 1/2" x 4/8ga	37.50%	62.50%	0.225/0.162		292	313	0.338	2.775	
	Duty 3-5-8	3" x 1/2" x 8ga Modified - Double Layer Mesh		56.00%	44.00%	0.162		315	338	0.338	0.338
	Duty 3-5-4M	3" x 1/2" x 4ga Modified - Double Layer Mesh		61.11%	38.89%	0.225		580	621	0.5	0.5

Description	Name	Size	Screening %	% Open Area	Thickness (Inches)		Lbs. per 100 S.F.		Short Opening Size (Inches)	Long Opening Size (Inches)
					Wire Thickness		Plain	Pre-Galv		
 SecuriGuard Woven Wire	Securi 34-162	3/4" x .162	38.50%	61.50%	0.162		229	229	0.588	0.588
	Securi 1-177	1" x .177	29.60%	70.40%	0.177		201	201	1	1
	Securi 2-225	2" x .225	11.25%	88.75%	0.225		146	146	2	2
	Securi 2-375	2" x .375	29.10%	70.90%	0.375		384	384	2	2
	Decorative Meshes Available									

Description	Name	Size	Screening %	% Open Area	Thickness (Inches)		Lbs. per 100 S.F.		Short Opening Size (Inches)	Long Opening Size (Inches)
					Strand Width	Strand Thickness	Plain	Galvanized		
 SentryGuard Expanded Wire	Sentry 34-9	3/4" x #9	32.00%	68.00%	0.15	0.135	180	198	0.688	1.562
	Sentry 1-7	1" x #7	48.00%	52.00%	0.24	0.179	360	378	0.576	1.5
	Sentry 112-6	1-1/2" x #6	31.00%	69.00%	0.203	0.198	250	275	1.11	2.313
Decorative Meshes Available										

Description	Name	Size	Screening %	% Open Area	Thickness (Inches)		Lbs. per 100 S.F.		Short Opening Size (Inches)	Long Opening Size (Inches)
					Strand Width	Strand Thickness	Plain	Galvanized		
 LouverMesh	MiniLouver 75	MiniLouver 75	75.00%	25.00%	0.188	0.09	282	310	0.25	0.8
	LouverMesh 94	LouverMesh 94	94.00%	6.00%	0.577	0.059	295	340	0.325	1.75

Description	Name	Size	Screening %	% Open Area	Thickness (Inches)		Lbs. per 100 S.F.		Short Opening Size (Inches)	Long Opening Size (Inches)
					Panel Thickness		Plain	Galvanized		
 StrikeGuard Perforated Metal	Strike 12-48	1/2" D, 11/16" STC, 2.45 H/SQI, 48% Open	52.00%	48.00%	0.12		260	278	0.5	0.5
	Strike 34-51	3/4" D, 1" STC, 1.1 H/ SQI, 51% Open	49.00%	51.00%	0.57		123	132	0.75	0.75

Description	Name	Size (alternating horizontal wires)	Screening %	% Open Area	Thickness (Inches)		Lbs. per 100 S.F.		Short Opening Size (Inches)	Long Opening Size (Inches)
					Panel Thickness		Plain	Galvanized		
 Securifor 4D Weldmesh	Securifor 4D	3" x 1/2" x 8ga	36.00%	64.00%	0.162		210	225	0.338	2.838

Options illustrated are standard configurations. Other mesh options and configurations are available.

Europe  
 Blokkestraat 34b  
 B-8550 Zwevegem  
 Tel: B: +32 56 73 46 46  
 Tel: NL: 0800 022 76 98

USA  
 3309 SW Interstate 45  
 Ennis, TX 75119  
 Tel: +1 972 878 7000  
 +1 888 650 4766



Middle East  
 P.O. Box 293517 DAFZA,  
 Building E 5, Block A  
 8th Floor, Office 802  
 Tel: +971 04 6091122

Africa  
 B10, Bergriver Business Park  
 Paarl,  
 7646  
 Tel: +27 021 868 7300

Betafence is the world market leader in fencing solutions, access control and detection for perimeter protection. All Betafence companies and product names are trademarks owned by PRÆSIDIAD Group Limited. Modification in products and assortment are subject to change without prior notice.

Proud to be a PRÆSIDIAD brand, Betafence is part of a global network, working alongside Guardiar and Hesco as a leader in perimeter security systems and solutions. For more information please visit praesidiad.com.

**B** **BETAFENCE**  
 Securing What Matters  
 info@betafence.com | betafence.com