



## Securifor® 358 Dublo

### Flat Panel

A flat panel reinforced with double vertical wires for increased intrusion resistance and security.

### Product detail



### FEATURES & BENEFITS

#### Proven resistance against cutting attempts

An additional vertical wire welded onto the back of the panel increases its resistance to cutting attempts by 30%. This longer delay time is critical in high-security environments where it is essential to intercept and stop breach attempts.

#### Forced entry and ballistic resistant

Securifor® 358 Dublo is independently tested at an accredited facility to ASTM F2781-10 standards for forced entry and ballistic resistance. Certificates available on request.

#### Visibility

Despite the small mesh apertures, the fence appears almost invisible from a distance, even at an angle. It is ideal for use with surveillance systems.

#### Compliant 3m wide panels

Panel widths meet the maximum distance requirement for electrical fence installation compliance.

#### Full system 10-year guarantee (standard terms & conditions apply)

Superior coatings underpin our 10-year anti-corrosion guarantee when Betafence's full system (panels, posts, and stainless steel fixators) is used.

### Security level



### Applications



### Functionalities

## Panels

Wire Diameter: 3.96mm Zinalu® Super (4.40mm PVC coated)

Apertures: 76.2mm x 12,7mm

Standard Widths: 3050mm

Heights: 2400mm, 3000mm

Tensile Strength: 500-750 N/mm<sup>2</sup>

Weld Strength: 50%

Weight: 10.61 kg/m<sup>2</sup>

## Gates

For comprehensive access control solutions that ensure a uniform level of security throughout your perimeter, inquire about our fit-for-purpose range of swing and sliding gates.

## Quality Assurance

Our range of high-security products are locally manufactured in our South African ISO 9001:2015 quality certified facility.

## Durable High-Quality Coatings



Highly durable Zinalu® Super and optional PVC coatings guarantee an extra-long lifespan and low maintenance, delivering extreme protection in even the harshest environments.

Available in Zinalu® Super only or with an additional PVC coating on panels in green RAL 6005 or anthracite RAL 7021.

## Posts & Fixing Mechanisms



Angle Iron Posts:

3m posts: 70mm x 70mm x 6mm

3.6m post: 100mm x 75mm x 6mm

Cover plate: 70mm x 6mm

Made from a rolled sheet, then hot-dip galvanized and PES coated RAL 6005 Green or RAL 7021 Anthracite.

To protect against tampering, the panel's edges are covered by a cover plate secured with stainless steel tamper-proof security bolts and shear-off nuts, firmly bolted through the post.

This combination of Betafence panels, posts and superior fixing mechanisms delivers a complete fencing system that ensures the installation's integrity and protection levels.

A top and / bottom rail adds rigidity to the fence line and further discourages climb over attempts.

## Additional Security Accessories

Extended posts and brackets are available to accommodate additional security features such as electric fencing\*, flat wrap razor, or BTC coil topings.

\*Supplied and installed by third parties.

### SECURIFOR 358 DUBLO (SOUTH AFRICA)

Nominal fence height (mm)	Panels		Intermediate & end posts		Corner posts	
	Width x Height (mm)	Bottom Rail (mm)	Angle Iron Profile (mm)	Height (mm)	Angle Iron Profile (mm)	Height (mm)
2400	3050 x 2375	2996 x 40 x 40 x 3	70 x 70 x 6	3000	70 x 70 x 6	3000
3000	3050 x 2985	2996 x 40 x 40 x 3	100 x 75 x 6	3600	100 x 75 x 6	3600

Other panel heights available on request (MTO)



Betafence is the world market leader in fencing solutions, access control and detection for perimeter protection. All Betafence companies and product names are trademarks owned by PRÆSIDIAD Group Limited. Modification in products and assortment are subject to change without prior notice.

Proud to be a PRÆSIDIAD brand, Betafence is part of a global network, working alongside Guardiar and Hesco as a leader in perimeter security systems and solutions. For more information please visit praesidiad.com.

**BETA FENCE**  
Securing What Matters

betafence.com/contact