



Roll Top®

Panels

A welded mesh panel fence incorporating rolled top and bottom edges for enhanced safety and rigidity.

Product details



BENEFITS

RoSPA Compliant

Ideal solution for schools and playgrounds.

Fast installation

All components have been specifically developed to provide a professional product of high quality that can be installed efficiently and rapidly.

Rigidity

The rolled beam profile at the top and bottom edge of each panel results in maximum rigidity.

Suitable where safety is a consideration

The principal feature of the panel is the unique rolled beam section at the top and bottom edge. The open mesh profile is also decorative and allows excellent through visibility with no finger or head traps. These safety features make Roll Top ideal for playgrounds, play areas and parks.

Security Level

Low - Medium

Applications



Functionalities

Post and fixing systems

The Roll Top system can be used with several post systems:



Twifix Post system

Universal powder coated square post to fit all low to medium security panels.

The panels are fixed on the front side of the posts by means of inserts, fixators and security bolts. The welded square tubular posts (60 x 60mm) are covered with a plastic cap.



Bekafix Post system

A unique, patented section design providing an aesthetic, smooth finish with easy installation. The panels are fixed laterally onto the powder coated posts and secured with anti-vandal metal security fixators. Supplied complete with a polyamide cap, a range of optional extras are also available.

Maximum height

To achieve fence heights above 1.8m the panels are designed for multi-lift erection i.e. one or more panels are placed above the bottom panel. Multi-lift brackets are required for heights above 1.8m.



Panels

The panels are 3000mm wide and heights range from 900 to 1800mm. The panels have a unique and 'user friendly' closed beam section located along the top and bottom edge of the panel. With no sharp or raw edges, Roll Top panels are suitable where safety is a consideration. Mesh sizes are 150 x 50mm, and panels are manufactured from heavy 5mm wires, to achieve highly rigid panels.

Gates

Panels can be easily combined with our Robusta swing gates as well as our sliding gates range.

Coating technique

Panels are manufactured from galvanised wires. An adhesion coating is applied to allow perfect adhesion with the polyester coating (min. 100 micron).

Colours

Roll Top is available as standard in green RAL 6005. Black RAL 9005 and other colours are available on request.

ASSORTMENT ROLL TOP

Fence height mm	Panels width x height mm
900	3000 x 900
1200	3000 x 1200
1500	3000 x 1500
1800	3000 x 1800
2400*	3000 x 1200 x 2

*Made to order.

