



Securifor® Super 6

Panels

Securifor Super 6 combines all the features of the Securifor 358, but offers an enhanced anti-cut performance using 6mm vertical wires.

Product details



BENEFITS

Secure and discreet

A superior system for providing security where a discreet visual impact on the immediate environment is essential.

Vandal resistant – anti-climb / anti-cut

The finger-proof aperture combined with a thicker 6mm wire diameter provides a stronger, more superior barrier that is difficult to climb and break through and highly resistant to cutting with conventional bolt or wire cutters.

Efficient deterrent

An effective deterrent to intruders, available in various heights up to 6m – specially designed for high security applications. Compatible with electronic alarm and detection systems.

Complete System

Supplied as a complete system with panels, post systems and gates.

Good viewing visibility

The panels have excellent visibility characteristics, due to the flat two-dimensional profile the fence appears almost invisible. This is particularly important for unobstructed camera surveillance, either from the front or at an angle.

Security Level

High

Applications



Functionalities



Post and fixing systems

Securifor Super 6 can be installed with a selection of post types:



Securifor Post system - Super 6

Posts designed to suit the Securifor panel range, combining high security with ease of installation and fixing methods. The posts are holed for bolt through fixing, the panels are fixed using a 25 x 5mm slotted clamp bar, M8 galvanised cup square round bolts and shear nuts. The welded tubular posts (60 x 60mm, 80 x 60mm, 80 x 80mm or 120 x 60mm depending on fence height) are covered with a plastic top cap.



Bekafix Super Post system – Super 6

A unique, patented, section design providing an aesthetic, smooth finish with secure installation, with added strength for higher level security projects. The panels are fixed laterally onto the powder coated posts and secured with anti-vandal metal security fixators with bolts. Supplied complete with a polyamide cap, a range of optional extras are also available.



Bekasecure Post system - Super 6

The Bekasecure post's design and high yield strength steel provide the ultimate in high security, rigidity and ease of installation. Posts are 10 x 20mm and the fixation of the panels is secured by the use of a continuous cover plate and specific security bolts. The open profile of the post allows electrical or fibre optic cabling and is closed with a specific metal cap.
Post Profile: 140 x 135 x 4mm (up to 6m fence height).

Panels

The panels are 2515mm wide and heights range from 1200 to 5200mm. Mesh sizes are 76.2 x 12.7mm and manufactured from 4mm horizontal wires and 6mm vertical wires. Minimum average weld shear strength 70% (tensile range 540 – 690 N/m²). Featuring a toe and finger proof mesh aperture, this system combines an anti-climb and anti-cut fence with excellent through visibility and resistance to vandalism. Extra length panels can be supplied (+300mm) for below ground to prevent burrowing.

Gates

The Securifor system can be supplied complete with Securifor swing and sliding gates for optimal protection.

Coating technique

Panels are manufactured from pre-galvanised wires. An adhesion coating is applied to allow perfect adhesion with the polyester coating (min. 100 micron). Posts are polyester coated with a galvanised substrate.

Colours

Securifor Super 6 is available as standard in green RAL 6005. Black RAL 9005 and other colours are available on request.

ASSORTMENT SECURIFOR SUPER 6

Fence height mm	Panels width x height mm
3300	2515 x 3300

Other sizes available on request.



Secured by Design options available.
Please contact the office for further details.