

## O-LOX® posts

### Posts

Rigid post system with cover plate or stainless steel fixing plate.

Variable fixing systems and post caps.

### Product detail



with cover plate



with stainless steel fixing plate

### BENEFITS

- 3 different fixing systems for 1 standard post
- Possibility to choose the post cap
- Steps of 200 mm

#### Profile

- Posts are foreseen of inserts every 200 - 400 mm
- PA clamps to support the panels are fixed to the posts with inserts M8
- Cross section post: 60 x 40 mm
- Plate thickness: 1.50 mm or 2 mm, depending on the height of the fence
- I/V 1.5 mm = 5.0 cm<sup>3</sup>
- I/V 2.0 mm = 6.19 cm<sup>3</sup>

#### Accessories

- Posts can be covered with post caps with or without overhang
- Flat steel cover plates (40x4mm)
- Stainless steel fixing plates of butterfly fixators
- Cover plate or fixing plates are bolted to the post with stainless steel bolts M8x40
- Corner clamps



#### Coating technique

Galvanised in-and outside (275 g/m<sup>2</sup> - both sides combined) and plastic coated (min. 60 micron)



#### Colours

Standard available in galvanised execution, in green (RAL 6005) and grey (RAL 7016).

#### Options

Posts can also be delivered with welded floorplates.

#### O-LOX® POSTS

Panel height mm	Post section mm	Post length mm	Inserts
630	60 x 40 x 1.5	1000	3
830	60 x 40 x 1.5	1300	4
1030	60 x 40 x 1.5	1500	4
1230	60 x 40 x 1.5	1700	5
1430	60 x 40 x 1.5	2000	5
1630	60 x 40 x 1.5	2200	6
1830	60 x 40 x 2	2400	6
2030	60 x 40 x 2	2600	7
2230	60 x 40 x 2	2800	7
2430	60 x 40 x 2	3000	8

### Compatible products

- Nylofor 2D/2DS

